


Technical info Flexile

Level of use 23 / 33 / 42 (EN ISO 10874)	Dimensional stability Pass ≤ 0.25% (EN ISO 23999)	Thermal resistance 0.0098 m ² -K/W (ISO 8302)	10 YEARS 10 year warranty commercial
Geometrical characteristics Compliant (ISO 24342)	Colour fastness to light ≥ grade 7 (ISO 105-B02)	Curling after exposure to heat ≤ 0.2 mm (EN ISO 23999)	 
Wear resistance Pass 5000 cycles (EN 13329 Annex E)	Impact sound reduction $\Delta L_w = 2$ dB (ISO 10140-3 / EN 717-2)	VOC Emissions Under detection limits (EN 16516)	
Castor chair resistance Pass 25000 cycles (ISO 4918)	Formaldehyde emission class E1 (EN 16516)	Content of Pentachlorophenol < 0.02 mg/kg (EN 12673)	
Effect of furniture leg No visible change (EN 16581)	Fire classification Bfl - S1 (EN 13501-1)	Chemical resistance Excellent resistance (EN ISO 16987)	
Residual indentation ≤ 0.10 mm (EN ISO 24343-1)	Slip resistance DS - R10 (EN 13893 - DIN 51130)	Underfloor heating Suitable (see: Underfloor Heating Guidelines)	
Resistance to staining 5 (no visible change) (EN 438-2)	Electrostatic performance ≤ 2 kV (EN 1815)		